

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
28 April 2005 (28.04.2005)

PCT

(10) International Publication Number
WO 2005/038319 A1

(51) International Patent Classification⁷: **F16K 5/22**

(21) International Application Number:
PCT/IB2004/003431

(22) International Filing Date: 19 October 2004 (19.10.2004)

(25) Filing Language: Italian

(26) Publication Language: English

(30) Priority Data:
MI2003A002035 20 October 2003 (20.10.2003) IT

(71) Applicant (for all designated States except US): **GALLI & CASSINA S.P.A.** [IT/IT]; Via Canova, 39, I-20145 Milano (IT).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **CASSINA, Francesco** [IT/IT]; Via Pietro Tamburini, 6, I-20123 Milano (IT).

(74) Agent: **MODIANO, Guido**; Modiano & Associati, Via Meravigli, 16, I-20123 Milano (IT).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

[Continued on next page]

(54) Title: **PLUG VALVE WITH LUBRICATION MEANS**



(57) Abstract: A plug valve with improved lubrication elements comprising a valve body (2), which forms a seat (3) that is connected to an intake port (5) and to a discharge port (6), and accommodates a plug-type flow control element (4) that controls the ports (5, 6). Lubrication elements are further provided between the seat (3) and the plug-type flow control element (4); the plug valve further comprising at least one pair of open lubrication channels (10), which are provided diametrically in the plug-type flow control element (4), and at least one pair of open lubrication ducts (20), which are provided diametrically in the seat (3). The pair of open channels (10) is always in contact with the seat (3) during the transfer of the plug-type flow control element from the open position to the closed position, and/or vice versa.

WO 2005/038319 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.